

SIGNALLING PANEL LB15

The signalling panel is equipped with:

- 15 LED-lights (L2H) ϕ 120 each provided with multileds
- Dimensions: Height 1,55 m / Width 1,10 m
- Full plated in an aluminium plate of 3 mm
- The panel has red/white retroreflective striping
- The panel is equipped with 15 LED-lights to form:
 - 1) light arrow left
 - 2) light arrow right
 - 3) cross

These are controlled by a control switch

- With PLC control (so no prints)

The light arrow is controlled via controllers making printed circuit boards are unnecessary (the controllers are not sensitive to temperature variations - 40 ° + 60 °)

- During the working position (example 2) you get a right light arrow, then 2 x blink of the 4 corner flashing lights and back the right light arrow etc. At the same time the blue arrow ϕ 700 mm is rotated in the correct position.
- For all these functions the arrow sign automatically rotates to the position of the selected arrow
- Operation from the cabin of the truck incl. +/- 15 m connection cable
- 12 or 24 V
- Automatic dimming



STUER-EGGHE

www.stuer-egghe.be

botsabsorbeers • daksignalisatie
mobiele signalisatie • aanhangwagens • metaalconstructies

Industriepark Noord 17a-23
9100 Sint-Niklaas

Tel 03/766.04.04
info@stuer-egghe.be